

PRODUCT: VLX Wash Luminaires

Subject: Reloading Factory Calibration Files (dropCal) in VLX™ Wash Luminaires

OVERVIEW

Below are special notes are for Authorized VARI*LITE® Service Centers and Dealers that wish to reload the original factory calibration files (**dropCal**) into VLXTM Wash Luminaires.



Note: This technical notice is for information purposes only. Owners and users are not required to inspect or make any repairs to their VARI*LITE® luminaires in response to this notice.

If you have any questions as to any aspect of this Technical Notice, please contact Vari-Lite customer service at 1-877-VARILITE or +1-214-647-7880.



WARNING: Any repairs or maintenance to VARI*LITE® luminaires should only be performed by a trained and qualified service technician or at an Authorized VARI*LITE® Service facility.

dropCal Special Notes

When reloading the original factory calibration files in VLXTM Wash luminaires, please observe the following:

- Only connect to one fixture at a time and follow the **dropCal** instructions outlined in the Maintenance Section of the VLXTM Wash Luminaire Service Manual.
- Make sure the **dropCal** file (obtained from Vari-Lite) matches the serial number of the fixture. The **dropCal** file is a unique calibration file and is specific to the fixture's serial number. Using a dropCal file from another fixture will load a different calibration scheme and will cause the fixture to be out of calibration.
- When uploading the factory calibration files to multiple fixtures, you must completely close and relaunch the **dropCal** application on the PC between fixtures (this clears any data being sent from the application and ensures the correct file will be uploaded).
- It is not necessary to disconnect the USB dongle from the PC.

CONTACT INFORMATION

For more information on this technical notice or on VARI*LITE® products, please contact your Authorized VARI*LITE® Dealer or Vari-Lite customer service.

NOTICE NO. TN-287 **02 OCTOBER 2009**